



touchMATRIX Indicator DX350 / DX355

Frequency counter, -tachometer and -speed indicator with touchscreen and graphic display

Product Features:

- Multifunctional unit with several operating modes, e. g. speed or position indicator, counter, timer or stopwatch
- Universal inputs (HTL/TTL/RS422) for encoders / sensors with NPN / PNP / NAMUR characteristic
- Bright and high-contrast display with event-dependent color variations
- Emulation of a 7-segment display inclusively icons and units
- Intuitive and easy parameterization by plain text and touchscreen
- 24 V auxiliary output for encoder supply
- Input frequencies up to 1 MHz
- Linearization with 24 control points
- Numerous features, e. g. scaling, filtering, start-up suppression
- 3.78 x 1.89 inch norm panel housing and IP65 protection

Available Options:

DX350: Basic unit with HTL inputs (A, B), 3 control inputs
DX355: Basic unit with HTL / TTL / RS422 inputs (A, /A, B, /B), 3 control inputs

- Option **AC:** Power supply 115 ... 230 VAC
- Option **AO:** 16 bit analog output, 4 control outputs, serial RS232 interface
- Option **CO:** 4 control outputs, serial RS232 interface
- Option **RL:** 2 relay outputs

All options can be combined

Technical Specifications:		
Connections:	Connector type:	screw terminal, 1.5 mm ² / AWG 16
Power supply (DC):	Input voltage:	18 ... 30 VDC
	Protection circuit:	reverse polarity protection
	Consumption:	approx. 150 mA (unloaded)
	Fuse protection:	extern: T 0.5 A
Power supply (AC): (Option AC)	Input voltage:	115 ... 230 VAC (50 ... 60 Hz)
	Power consumption:	approx. 3 VA (unloaded)
	Fuse protection:	extern: T 1.0 A
Encoder supply:	DC version:	approx. 1 V lower than the power supply voltage
	Output current:	max. 250 mA
	AC version:	approx. 24 VDC (± 15%)
	Output current:	150 mA until 45°C / 80 mA by more than 45°C
Incremental inputs: (DX350)	Number of inputs:	2
	Configuration:	PNP-, NPN-, Namur or Tri State
	Channels:	A, B
	Format:	HTL (Low 0 ... 3 V, High 9 ... 30 V)
	Frequency:	max. 250 kHz
	Load:	max. 6 mA / Ri > 5 kOhm / 470 pF
Incremental inputs: (DX355)	Number of inputs (channels):	4 (A, /A, B, /B)
	Configuration single-ended:	TTL or HTL (max. 250 kHz)
	Format single-ended:	TTL (Low 0 ... 0,8 V, High 2 ... 10 V) HTL (Low 0 ... 6 V, High 8 ... 30 V)
	Configuration differential:	TTL (RS422) or HTL (max. 1MHz)
	Format differential:	TTL (RS422) differential signal > 0,5 V HTL differential signal > 2 V
	Load:	max. 2 mA / Ri > 10 kOhm / 47 pF
Control inputs:	Number of inputs:	3
	Format:	HTL, PNP (Low 0 ... 3 V, High 9 ... 30 V)
	Frequency:	max. 10 kHz
	Load:	max. 2 mA / Ri > 15 kOhm / 470 pF
Analog output: (Option AO)	Configuration:	current or voltage operation
	Voltage output:	-10...+10 V (max. 2 mA)
	Current output:	0/4 ... 20 mA (burden: max. 270 Ohm)
	Resolution:	16 Bit
	Accuracy:	± 0,1 %
Control outputs: (Option CO)	Number of outputs:	4
	Format / level:	5 ... 30 V (depends on the COM+ voltage), PNP
	Output current:	max. 200 mA
	Reaction time:	< 1 ms
Relay outputs: (Option RL)	Number of outputs:	2
	Configuration:	potential free changeovers
	AC-Switching capacity:	max. 250 VAC / 3 A / 750 VA
	DC-Switching capacity:	max. 150 VDC / 2 A / 50 W
	Reaction time:	< 5 ms
Serial interface: (Option CO)	Format:	RS232
	Baudrate:	9600, 19200 or 38400 baud
Display:	Type:	LCD (backlight)
	Display range:	8 digits plus sign (-99999999 ... 99999999)
	Digit height:	13 mm height
	Color:	red / green / yellow (switchable)
	Operation:	resistive touchscreen
Housing:	Material:	ABS, UL 94 V-0
	Mounting:	panel cut out
	Dimensions (w x h x d):	96 x 48 x 116 mm / 3.78 x 1.89 x 4.56 inch
	Cut out (w x h):	91 x 43 mm / 3.58 x 1.69 inch
	Protection class:	IP65 (front), IP20 (rear)
	Weight:	approx. 200 g
Ambient temperature:	Operation:	-20°C ... +60°C resp. -4 ... 140°F
	Storage:	-25°C ... +70°C resp. -13 ... 158°F